

## 6552 GX Wiwa 52:1 6.5 L/min

SKU: L214005



For industrial shops spraying lacquer, varnish, metal primer, finish enamels, etc. Available for wall mounting, cart mounting, or lid mounting. Quiet running air powered motor is safe for hazardous locations. Packings are spring loaded and automatically adjust for extra long life. Packing fluid chamber is totally enclosed and packings are stationary to eliminate cylinder wear.

**Features:**

- Fluid passage in stainless steel
- Stationary spring loaded pump packings which automatically adjust themselves.
- Fluid valves are made of abrasion resistant tungsten carbide and stainless steel.
- Large area mufflers to maintain quiet operating surroundings.
- Consistent spray pressure provides an excellent spray pattern
- Design with few wear parts, designed for easy maintenance
- A closed flushing agent chamber separates air motor and fluid pump. The flushing material prevents encrustations of paint on the piston rod and with its lubricating effect protects the seals.

**Specifications:**

- Ratio: 52:1 (~5200 psi fluid @ 100 psi air)
- Air inlet max 116 PSI
- Air use: 27 cfm@ 100 psi with 0.023 tip
- Free Flow Volume: 1.7 GPM (max) (6.5 L/min)
- Maximum pressure: 6000 PSI
- Maximum Recommended Speed: 65 cycles/min
- Tip: 1x 0.029" (max), 2x 0.021" or 5x 0.013"
- Height: 31.5" (bare)
- Weight: 40 lbs (bare)