



LA3600 Air Assist Kit 4233

This commercial duty wall mounted system uses a SKU: L011040 combination of airless fluid pressure (500 - 3300 psi) and low atomizing air pressure (5 - 50 psi) to give the very best of both air and airless technologies resulting in fast production speeds with top quality finishes. Air-airless systems also have the advantage of pumping from the original container and easy to clean. Our high quality system features the European made LA3600 gun for ultimate reliability. This compact gun has a soft trigger-pull to reduce operator fatigue and is lightweight and easy to maneuver.

Features:

- Soft spray pattern with low bounceback
- Reduced overspray with increased control
- Premium quality Wiwa stainless steel pump
- Gun is lightweight and comfortable
- Flexible suction draws from original pail
- System is easy to clean and maintain
- Handles low to medium viscosity materials
- Versatile - compatible with waterbase or solvent base products
- Supported by Lemmer parts and service across Canada for over 40 years

Applications:

- Ideal for waterbase products, stains, varnishes, primers, lacquers, catalyzed urethane
- Fine wood furniture and cabinetry
- Metal furniture, doors, cabinets, lockers
- Trucks, cars, motorhomes, buses - manufacturing and repainting
- Industrial and farm equipment
- Machinery and HVAC manufacturing
- Aircraft
- Ships and boats

Benefits:

- Reduced material use means less cost
- Reduced emissions help meet government regulations
- Upgrade your plant to new waterbase materials
- Reduced overspray = less booth maintenance
- Cleaner work environment
- Increased productivity

[Part Diagram LA-3600](#)

[Owner Manual Pump 4233](#)

[Part Diagram Fluid Section 4233](#)

[Part Diagram Air Motor 4233](#)

kit included

- wiwa pump 33:1 , 4,2L/min
- wall bracket
- 5G suction system 1/2"
- 28' hose 3/16"
- Whip 1/8" x 3'
- LA-3600 Air assist gun with guard and tip

Specifications

System Specifications:

Max air input pressure: 115 psi
 Air use, typical: 7-10 cfm
 Suction hose length: 4 ft x 1/2" ID, nylon lined
 Fluid/air hose, supplied: 28ft.(3'x1/8" whip incl.)
 Shipping size: 25"L x 15"W x 12"H
 Shipping weight: 37 lbs

Wiwa 4233 Pump :

Ratio 33:1
 Air input pressure: 15-125 psi
 Max sys pressure: 3300 psi
 Free flow volume: 1.1 gpm
 Air consumption: 2 - 7 cfm

Air Assist gun LA3600:

Maximum Fluid pressure: 3600 psi.
 Maximum Air pressure: 125 psi.
 Fluid inlet: 1/4" NPS-M
 Air inlet: 1/4" NPS-M
 Required air: 2 - 15 cfm
 Weight: 19 ounces
 Wetted parts: SS,TC,Nyl,Tef.

